

也址:中国广东省广州市天河区珠江新城花城大道66号B座

Add.: Tower B, No.66 Huacheng Avenue, Zhujiang Xincheng, Tianhe District, Guangzhou,Guangdong, P.R.C

邮箱Email: ppdc@iqtcnet.cn 网址Website: https://www.iqtcnet.cn

01112200004264-2(E)

2022-12-31

材料安全数据表 **Material Safety Data Sheet**

Sample Name: **Power Lite-U**

深圳昱泽新能源有限公司 委托单位:

Shenzhen UZ Energy Limited Applicant:



I70YEEKHZB



本报告结果仅对测试样品负责。The results in this report are relevant only to the sample(s) tested. 未经签发机构书而同意,不得部分引述或复制本报告。Without written permission of IQTC, this report shall not be quoted or reproduced except in full. 本报告数据、结果仅限定为委托方内部使用,不具有对社会证明作用。The report is not legally binding and could only be used as internal reference material for the applicant.



GUANGZHOU CUSTOMS DISTRICT TECHNOLOGY CENTER

地址:中国广东省广州市天河区珠江新城花城大道66号B座 邮编Postcode: 510623

Add.: Tower B, No.66 Huacheng Avenue, Zhujiang Xincheng, Tianhe District, Guangzhou, Guangdong, P.R.C.

01112200004264-2(E) No:

Date: 2022-12-31

材料安全数据表

Material Safety Data Sheet

A POLY	1. 化学品及企业标识				
CHE	MICAL PRODUCT AND COMPANY IDENTIFICATION				
样品名称	储能单元				
Sample Name	Power Lite-U				
型号 Model	L051100-B				
委托单位	深圳昱泽新能源有限公司				
Applicant	Shenzhen UZ Energy Limited				
委托单位地址 Applicant Address	深圳市福田区梅林街道梅丰社区梅华路 105 号多丽工业区 2-3 栋 3 栋 3 层 313 房 ROOM313, 3F 3BLOCK, DUOLI INDUSTRIAL ZONE, 105#MEIHUA RD.,SHANGMEILIN, FUTIAN DISTRICT, SHENZHEN				
生产单位	深圳昱泽新能源有限公司				
Manufacture	Shenzhen UZ Energy Limited				
生产单位地址 Manufacture Address	深圳市福田区梅林街道梅丰社区梅华路 105 号多丽工业区 2-3 栋 3 栋 3 层 313 房 ROOM313, 3F 3BLOCK, DUOLI INDUSTRIAL ZONE, 105#MEIHUA RD.,SHANGMEILIN, FUTIAN DISTRICT, SHENZHEN				
应急电话 Emergency telephone call	13269776666				

2. 成分/组成信息

COMPOSITION INFORMATION

. 2	JULE OFFICE	12 0241.2122011	
成分 Hazardous components	含量/% Content / %	CAS NO.	备注 Remark
Graphite	7-25	7782-42-5	OURT-
Lithiumiron Phosphate	15-40	15365-14-7	THE TOTAL STATE
Hexafluoropropylene-vinylidene fluoride Copolymer	3-15	9011-17-0	ELE THEOLOGY
Lithium Hexafluorophosphate	0-5	21324-40-3	AICTARD US DISTRA
Acetylene Black	0-2	1333-86-4	5 DIST I CUSTON JIETHO
Diethyl Carbonate	0-15	105-58-8	, and thou enay
Dimethyl Carbonate	0-15	616-38-6	Cn.
Ethyl Methyl Carbonate	0-15	623-53-0	OGT CELL CHINOLO

^{1.} 本报告结果仅对测试样品负责。The results in this report are relevant only to the sample(s) tested. 2. 未经签发机构书面同意,不得部分引述或复制本报告。Without written permission of IQTC, this report shall not be quoted or reproduced except in full. 3. 本报告数据、结果仅限定为委托方内部使用,不具有对社会证明作用。The report is not legally binding and could only be used as internal reference material for the applicant.



GUANGZHOU CUSTOMS DISTRICT TECHNOLOGY CENTER

也址:中国广东省广州市天河区珠江新城花城大道66号B座 邮编Postcode: 510623

Add.: Tower B, No.66 Huacheng Avenue, Zhujiang Xincheng, Tianhe District, Guangzhou, Guangdong, P.R.C.

电话Tel: 020-22131000 邮箱Email: ppdc@iqtcnet.cn 网址Website: https://www.iqtcnet.cn

01112200004264-2(E) No:

Date: 2022-12-31 3 of 9 Page:

Propylene Carbonate	0-15	108-32-7	JOHNS THOUGH	CURIC
Ethylene Carbonate	0-15	96-49-1	CINAL	

3. 危险性概述

Hazards Identification





9类锂电池

Class 9- Lithium batteries

爆炸危险性 该物品不属于爆炸危险品。

Explosive risk This article does not belong to the explosion dangerous goods.

易燃危险性 该物品不属于易燃危险品。

Flammable risk This article does not belong to the flammable material.

氧化危险性 该物品不属于氧化危险品。

Oxidation risk This article does not belong to the oxidation of dangerous goods.

毒害危险性 该物品不属于毒害危险品。

Toxic risk This article does not belong to the toxic dangerous goods.

放射危险性 该物品不属于放射危险品。

Radioactive risk This article does not belong to the radiation of dangerous goods.

腐蚀危险性 该物品不属于腐蚀危险品。

Mordant risk This article does not belong to the corrosion of dangerous goods.

其他危险性 该电池瓦时率5.1kWh, 属于锂离子电池。

other risk Watt hour rate 5.1kWh, which belong to the Lithium-ion battery.

4. 急救措施

First aid measures

万一接触,立即用大量的清水冲洗至少 15 分钟,翻起上下眼睑,直到化学的残留物消失为止,迅速就医。

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

万一接触,用大量水冲洗至少 15 分钟,同时除去污染的衣物和鞋子,迅速就医。

Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes

Get medical aid.

立即从暴露处移至空气清新处,如果呼吸困难给予输氧,立即就医。

Remove from exposure and move to fresh air immediately. Use oxygen if available.

- results in this report are relevant only to the sample(s) tested. 達或复劇本报告。Without written permission of IQTC, this report shall not be quoted or reproduced except in full.
- 不具有对社会证明作用。The report is not legally binding and could only be used as internal reference material for the applicant.



GUANGZHOU CUSTOMS DISTRICT TECHNOLOGY CENTER

也址:中国广东省广州市天河区珠江新城花城大道66号B座 邮编Postcode: 510623

Add.: Tower B, No.66 Huacheng Avenue, Zhujiang Xincheng, Tianhe District, Guangzhou, Guangdong, P.R.C.

电话Tel: 020-22131000 邮箱Email: ppdc@iqtcnet.cn 网址Website: https://www.iqtcnet.cn

01112200004264-2(E) No:

Date: 2022-12-31

Page:

引用两杯牛奶或水。如果当事人仍然清晰可以采取催吐的方法, 并且立即就医。

Ingestion

Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician

5. 消防措施

Fire-fighting measures

燃点:不适用

Flash Point: N/A. 自燃温度:不适用

Auto-Ignition Temperature: N/A.

灭火介质:大量水(降温),二氧化碳

Extinguishing Media: Water, CO2.

特殊灭火程序: 自给式呼吸器

Special Fire-Fighting Procedures: Self-contained breathing apparatus.

异常火灾或爆炸: 当电芯暴露于过热的环境中时,安全阀可能会打开。

Unusual Fire and Explosion Hazards: Cell may vent when subjected to excessive heat-exposing battery contents.

燃烧产生的危险物品:一氧化碳,二氧化碳,锂氧化物烟气

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

6. 泄露应急处理

Accidental release measures

为防止电池材料泄露或释放采取的措施

如果电池内部材料泄露,试验人员应立刻撤离试验区直到烟气消散。将通风设备打开吹散危险性气体。用抹布擦 净试验区,清除溢出的液体,将泄露电池放进塑料袋中,然后放进钢制容器。避免皮肤和眼睛接触或吸入有害气

Steps to be Taken in case Material is Released or Spilled

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can. The preferred response is to leave the area and allow the battery to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

废弃物处置方法

建议将电池完全放电,消耗电池内部的锂金属,并且深埋于土壤中。

Waste Disposal Method

It is recommended to discharge the battery to the end, to use up the metal lithium inside the battery, and to bury the discharged battery in soil.

The results in this report are relevant only to the sample(s) tested.

公司前以行动员员。 The results in this report are relevant only or sample, see the provided of the provided except in full. 为书面问意,不得部分引述或复制本报告。 Without written permission of IGTC, this report shall not be quoted or reproduced except in full. 结果仅限定为委托方内部使用,不具有对社会证明作用。The report is not legally binding and could only be used as internal reference material for the applicant shall not be provided as a notarial certification.



GUANGZHOU CUSTOMS DISTRICT TECHNOLOGY CENTER

也址:中国广东省广州市天河区珠江新城花城大道66号B座 邮编Postcode: 510623

Add.: Tower B, No.66 Huacheng Avenue, Zhujiang Xincheng, Tianhe District, Guangzhou, Guangdong, P.R.C.

电话Tel: 020-22131000 邮箱Email: ppdc@iqtcnet.cn 网址Website: https://www.iqtcnet.cn

01112200004264-2(E) No:

Date: 2022-12-31 Page: 5 of 9

7. 操作处置和储存

Handling and storage

禁止打开、毁坏或焚烧电池,因为电池有可能在这些处理过程中发生爆炸、破裂或泄露等事故。禁止将电池短路 过充、强制放电或扔入火中。禁止挤压刺穿电池或将电池浸入溶液中。

The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.

操作处置和储存中的防范措施

禁止物理或电滥用,禁止高温储存,最好将电池储存在阴凉、干燥、通风等温度变化较小的环境中。禁止将电池 接触加热设备或将电池直接暴露与阳光中。

Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

其他要注意的防范措施

拆解、挤压、直接放入火中或高温条件下,电池可能发生爆炸和燃烧。禁止短接或将电池正负极错误的安装在设 备中。

Other Precautions

The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

8. 接触控制/个人防护

Exposure controls/personal protection

呼吸防护:

当电池排气阀打开时,应尽量使通风设备开至最大,避免将打开排气阀的电芯局限在某一狭窄空间内。正常操作 条件下, 呼吸保护是不必要的。

Respiratory Protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use.

通风条件

正常使用条件下不需要。

Ventilation

Not necessary under conditions of normal use.

防护手套

正常使用条件下不需要

Protective Gloves

Not necessary under conditions of normal use.

其他防护服装或设备

正常使用条件下不需要。

Other Protective Clothing or Equipment

Not necessary under conditions of normal use.

电池开阀试验时应做好个人防护

呼吸防护, 防护手套, 防护服装和有护边的安全玻璃罩都是要准备的。

Personal Protection is recommended for venting battery

Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

The results in this report are relevant only to the sample(s) tested

ne results in this report are researching to the sample(s) resorts shall not be quoted or reproduced except in full. 分別述或复制未报告。Without written permission of IQTC, this report shall not be quoted or reproduced except in full. 分別述或支持,不具有对社会证明作用。The report is not legally binding and could only be used as internal reference material for the applicant 结果仅限定为委托方内部使用。



GUANGZHOU CUSTOMS DISTRICT TECHNOLOGY CENTER

也址:中国广东省广州市天河区珠江新城花城大道66号B座 邮编Postcode: 510623

Add.: Tower B, No.66 Huacheng Avenue, Zhujiang Xincheng, Tianhe District, Guangzhou, Guangdong, P.R.C.

电话Tel: 020-22131000 邮箱Email: ppdc@iqtcnet.cn 网址Website: https://www.iqtcnet.cn

01112200004264-2(E) No:

Date: 2022-12-31 Page:

9. 物理和化学特性

Physical and chemical properties

外形: 方形

Appearance: Quadrate shape 气味:泄漏时,有醚的气味。

Odors: If leaking, smells of medical ether.

酸碱度:不适用

pH: Not applicable as supplied.

燃点:除单个电芯暴露试验外其他不适用。

Flash Point: Not applicable unless individual components exposed.

可燃性: 除单个电芯暴露试验外其他不适用。

Flammability: Not applicable unless individual components exposed.

相对密度:除单个电芯暴露试验外其他不适用。

Relative density: Not applicable unless individual components exposed.

溶解性(水溶性):除单个电芯暴露试验外其他不适用。

Solubility (water): Not applicable unless individual components exposed.

溶解性(其他):除单个电芯暴露试验外其他不适用。

Solubility (other): Not applicable unless individual components exposed.

10. 稳定性和反应活性

Stability and reactivity

稳定性:产品在第 7 节所述的条件下稳定。

Stability: Product is stable under conditions described in Section 7.

应避免的条件: 加热 70℃ 以上或焚烧。变形。毁坏。粉碎。拆卸。过充电。短路。长时间暴露 在潮湿的条件下。

Conditions to Avoid: Heat above 70 °C or incinerate. Deform. Mutilate, Crush. Disassemble. Overcharge. Short circuit. Expose over a long period to humid conditions.

应避免的材料:氧化剂,碱,水。

Materials to avoid: Oxidising agents, alkalis, water. 危险分解物:有毒烟雾,并可能形成过氧化物。

Hazardous Decomposition Products: Toxic Fumes, and may form peroxides.

聚合危害: 不适用

Hazardous Polymerization: N/A.

如果发生泄露,避免与强氧化剂,无机酸,强碱,卤代烃接触。

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalies, halogenated Hydrocarbons

本报告数据、结果仅限定为委托方内部使用,不具有对社会证明作用。The report is not legally binding and could only be used as internal reference material for the applicant.



GUANGZHOU CUSTOMS DISTRICT TECHNOLOGY CENTER

也址:中国广东省广州市天河区珠江新城花城大道66号B座 邮编Postcode: 510623

Add.: Tower B, No.66 Huacheng Avenue, Zhujiang Xincheng, Tianhe District, Guangzhou, Guangdong, P.R.C.

电话Tel: 020-22131000 邮箱Email: ppdc@iqtcnet.cn 网址Website: https://www.iqtcnet.cn

01112200004264-2(E)

Date: 2022-12-31 Page:

11. 毒理学资料

Toxicological information

标志及症状:无,除非电池破裂。

Signs & symptoms: None, unless battery ruptures.

内部物质暴露的情况下,蒸汽烟雾可能对眼睛和皮肤的刺激性。

In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.

吸入:对肺有刺激性。

Inhalation: Lung irritant. 皮肤接触:对皮肤刺激性。 Skin contact: Skin irritant. 眼睛接触:对眼睛有刺激性。 **Eye contact:** Eye irritant

食入: 吞下中毒。

Ingestion: Poisoning if swallowed.

下列情况下健康状况会恶化:万一发生与电池内部材料接触的事故,轻微或严重的刺激,都可能使皮肤出现干燥 和灼烧的感觉,并且损坏靶器官(肝脏,肾脏)的神经。

Medical conditions generally aggravated by exposure: In the event of exposure to internal contents, moderate to server irritation, burning and dryness of the skin may occur, Target Organs nerves, liver and kidneys.

12. 生态学资料

Ecological information

对哺乳动物的影响:目前未知。

Mammalian effects: None known at present.

生态毒性:目前未知。

Eco-toxicity: None known at present. 生物体内积累:慢慢地生物降解。

Bioaccumulation potential: Slowly Bio-degradable.

环境危害:目前没有已知的环境危害。

Environmental fate: None known environmental hazards at present.

13. 废弃处置

Disposal consideration

不要焚烧,或使电池温度超过 70℃,这种滥用可导致泄漏和/或电池爆炸。按照相应的地方性法规处理。 Do not incinerate, or subject cells to temperature in excess of 70 °C, Such abuse can result in loss of seal leakage, and/or cell explosion. Dispose of in accordance with appropriate local regulations.

本报告结果仅对测试样品负责。The results in this report are relevant only to the sample(s) tested. 未经签发机构书面同意,不得部分引述或复制本报告。Without written permission of IQTC, this report shall not be quoted or reproduced except in full. 本报告数据、结果仅限定为委托方内部使用,不具有对社会证明作用。The report is not legally binding and could only be used as internal reference material for the applicant. shall not be provided as a notarial certification.



GUANGZHOU CUSTOMS DISTRICT TECHNOLOGY CENTER

也址:中国广东省广州市天河区珠江新城花城大道66号B座 邮编Postcode: 510623

Add.: Tower B, No.66 Huacheng Avenue, Zhujiang Xincheng, Tianhe District, Guangzhou, Guangdong, P.R.C.

电话Tel; 020-22131000 邮箱Email; ppdc@iqtcnet.cn 网址Website; https://www.iqtcnet.cn

01112200004264-2(E) No:

Date: 2022-12-31 Page:

14. 运输信息

Transport information

运输标签: 第九类危险品标签,

Label for conveyance: Class 9 Hazard Label,

UN编号: UN 3480 UN Number: UN 3480 运输专用名称: 锂离子电池

Proper Shipping name: Lithium ion batteries

包装导则: P903

Packing Instruction: P903

IMDG CODE 特殊规定: 230, 310, 348, 376, 377, 384, 387 IMDG CODE Special provisions: 230, 310, 348, 376, 377, 384, 387

EmS编号: F-A,S-I EmS No: F-A,S-I 海洋污染物:无

Marine pollutant: No

危害分类:货物应遵守联合国危险货物运输的建议书规章范本第二十二版和IMDG CODE (Amdt.40-20) 2020包

装导则P903的要求。包括通过UN38.3测试手册要求。

Hazard Classification: The goods shall be complied with the Packing Instructions TDG 22th Edition and the Packing Instructions P903 of IMDG CODE (Amdt.40-20) 2020 Edition, including the passing of the UN38.3 test.

本报告结果仅对测试样品负责。The results in this report are relevant only to the sample(s) tested. 未经签发机构书而同意,不得部分引述或复刺本报告。Without written permission of IQTC, this report shall not be quoted or reproduced except in full. 本报告数据、结果仅限定为委托方内部使用,不具有对社会证明作用。The report is not legally binding and could only be used as internal reference material for the applicant. It shall not be provided as a notarial certification.



GUANGZHOU CUSTOMS DISTRICT TECHNOLOGY CENTER

也址:中国广东省广州市天河区珠江新城花城大道66号B座 邮编Postcode: 510623

Add.: Tower B, No.66 Huacheng Avenue, Zhujiang Xincheng, Tianhe District, Guangzhou, Guangdong, P.R.C.

电话Tel: 020-22131000 邮箱Email: ppdc@iqtcnet.cn 网址Website: https://www.iqtcnet.cn

01112200004264-2(E) No:

Date: 2022-12-31 Page:

15. 法规信息

Regulation information

主要可适用锂电池运输的法律法规如下:

The laws and regulations applicable to the transportation of lithium batteries are as follows:

《联合国关于危险货物运输的建议书 规章范本》ST/SG/AC.10/1/Rev 22.

The UN Model Regulations, United Nations ST/SG/AC.10/1/Rev 22. Recommendations on the Safe Transport of Dangerous Goods

国际民用航空组织(ICAO)技术指令对于通过航空对危险货物的安全运输要求

The International Civil Aviation Organization (ICAO) Technical Instructions for the Safe Transport of Dangerous Goods by Air Transport

国际航空运输协会(IATA)危险货物运输规则(2023 版 64th)

The International Air Transport Association (IATA) Dangerous Goods Regulations (64th Edition 2023)

国际海事协会(IMO)国际海事危险货物规则(IMDG Code) 2020

International Maritime Organization (IMO) International Maritime Dangerous Goods Code (IMDG Code) 2020 《危险品公路运输欧洲协议》(2023年版)

UNITED NATIONS Recommendations on the Authorisation Dangerous Road Model Regulations (2023 edition) JT/T 617-2018《危险货物道路运输规则》

JT/T 617-2018 Regulations concerning road transportation of dangerous goods

16. 其他信息

Other information

本文件仅对由委托方提供的,并由深圳昱泽新能源有限公司生产的电池(型号:L051100-B)有效。该电池的成 分信息由委托方提供并承诺其完整性和准确性。

用户应仔细阅读此文件,并按照正确的方法使用电池,如因电池使用不当造成的损害或损失,广州海关技术中心 不承担任何责任。

This file is only effective to the batteries (Model: L051100-B) provided by commissioner which manufactured by Shenzhen UZ Energy Limited. The commissioner provides the composition information of batteries, and promises its integrity and accuracy.

Users should read this file carefully, and use the batteries in correct method. Guangzhou Customs District Technology Centre doesn't assume responsibility for any damage or loss because of misuse of batteries.

结束 End of report

भिक्त कि एक निर्देश कि प्रकार कि प